

Pedestrian Request Button Typ Broer Standard



Supply voltage:

10V; 24V; 42V; 230V

Color of enclosure:

Standard: yellow

Cap of the feedback module: red

Other colors for the enclosure are possible.

Installation:

Different adapter parts for the installation on poles with different diameters, also wall installation.

Marking symbols



BLIND,



FUSSGÄNGER,



RADFAHRER.

Functional modules
Structure / Configuration
Contact sensor

Contact-sensitive sensor area

LED signal area

Red flashing field made of maintenance-free LED, optionally adjustable on site: Flashing or continuous light

Tactile Signal Head

Tactile clearance signal by an axial-aligned vibration system with arrows as groping area on the underside of the enclosure

Buried Push Button

Push button with arrow as feedback area on the underside of the enclosure

Push buttons are available in the following combinations:

Type	Contact sensor	LED signal	Tactile signal head	Buried push button
A	X	X		
B	X			
C			X	X
D			X	
E	X	X	X	X
F	X	X		X
G				X
H	X			X
I	X		X	X

Signalbau Huber GmbH

Bodenseestrasse 113

D-81243 München

Tel.: +49 (0)89 / 89 699-100

Fax: +49 (0)89 / 89 699-331

E-Mail: info@signalbau-huber.de

Internet: www.signalbau-huber.de